



BAHRAIN NATIONAL STADIUM

Product Specifications

Structure

- Horizontal beam structure of 60mm X 40mm X 3mm thk.

Backrest and Seat

- Polypropylene.
- Flame retardant with U.V inhibitors.
- Built-in U.V inhibitors ensure no significant colour or plastic deterioration for a period of 5 years (BS EN ISO 4892 – Specification for U.V Stabilization).
- Ergonomically designed injection moulded high impact copolymer polypropylene with smoothly curved sat for comfort seating and easy maintenance.

Metal Finishing

- All metal parts exposed shall be stripped and cleaned with iron phosphate, hot water rinsed and then chromic acid rinsed.
- All metal parts are coated with an epoxy finish of at least 60 microns for indoor use and hot dipped galvanized to BS 729 for outdoor use.
- Conformity with BS-6496 hardness test.

Plastic Finishing

- Refer to Ferco plastic color chart.

Advantages

- Comfort especially studied according to fundamental criteria of ergonomic.
- Durability of the chair & after sales service for all spare parts of the model.
- Slim profile creating enhance seat way.
- Curved backrest design for maximum comfort.
- “Steel Beam Clamp” concept giving the ease of relocation of seats along the beam.
- Flexibility of seats by using the steel beam clamp for easy installation & maintenance.

Fire Resistance


- Flammability compliance with California Bulletin 117 and international regulations. in their last issues and particularly with safety régulations.

Warranty


- Refer to Ferco product warranty.

Additional Options

- ARC multi with P.U
- ARC multi plus
- ARC multi with cupholder
- ARC multi with retractable armrest
- ARC Wrimatic
- ARC Left hand armrest
- ARC end cap with row lettering
- ARC end cap with numbering
- ARC rectangular seat numbering
- Riser mounted leg
- Tier mounted leg
- Flammability compliance with BS 5852 : 2006 section 3 ignition source



H



C

DIMENSIONS	
H	C
750 (29.5")	450 (17.5")

450 (17.5") Min.