



FERCO SEATING ILLUSTRATION ONLY

Product Specifications

Structure

- Made up of Mild Steel hollow section in various sizes like: 19mm x 19mm x Thk1.6mm, 19mm x 38mm x Thk 2.0mm, Metal plate Thk 5mm and Ø19 x Thk 2.0mm.
- High durability non motorised gliding mechanism.

Backrest and Seat

- Glided backrest with inner structure made of Ø19mm x Thk 2.0mm metal frame with high resilience foam upholstered in leatherette / leather / fabric. Topped with backrest and headrest paddings made from high resilience foam upholstered in leatherette / leather / fabric.
- Glide Seat unit with inner structure made of Ø19mm x Thk 2.0mm metal frame with high resilience foam upholstered in leatherette / leather / fabric. Topped with seat padding made from high resilience foam upholstered in leatherette / leather / fabric.

Panel

- Combination of wooden ply, solid wood, and a mild steel frame. Then topped with high resilience foam upholstered in leatherette / leather / fabric and accompanied with cupholder.

Metal Finishing

- All metal parts exposed shall be stripped and cleaned with iron phosphate, hot water rinsed and then chromic acid rinsed.
- All metal parts are coated with an epoxy finish minimum of 60 microns for outdoor use.

Upholstery Finishing

- Refer Ferco standard fabrics / leatherette / leather chart.

Fire Resistance


- Fire Safety - Flammability compliance with California Bulletin 117 and international regulations in their last issues and particularly with safety regulations.
- Flammability compliance with BS 5852 : 2006 Section 3 Ignition Source 0 & 1.

Warranty


- Refer to Ferco product warranty.

Options

- Swivel table A
- Swivel table B
- Double action swivel table
- Dual USB charging port
- Embroidery logo
- Embroidery seat numbering
- Square light row lettering & numbering (80 x 80mm)
- Puck light
- Flammability compliance with BS 5852 : 2006 Section 3 Ignition Source 5



650 (25.5")



C

DIMENSIONS	
H	C
1040 (41")	800 (31.5")