


500 (19.5") 510 (20")
520 (20.5") 530 (20.9")
540 (21.3") 550(21.7")



R

H

C

DIMENSIONS	
H	840 (33")
C	460 (18")
R	700 (27.5")



Oxford Playhouse, United Kingdom

Product Specifications

Structure

- Structure with prongs to set proper backrest angle, ranging from 4° to 37°.
- Seat pan articulation system by patented blade system. Especially silent soft close tip-up, no maintenance required.

Backrest and Seat

- Ergonomic form with good lumbar support.
- Internal structure of 13.5mm - plywood with multiple layers and plastic sliding insert.
- Polyurethane fire retardant foam, cold moulded, density of 25 to 30 Kg/m³.
- Seat is of polyurethane fire retardant foam, cold-moulded, density of 50 to 55 Kg/m³, moulded onto a metal support.

Panel / Armrest

- Internal wooden structure with polyurethane foam, density 118 Kg/m³.

Metal and Fabric Finishing

- All metal parts exposed shall be stripped and cleaned with iron phosphate, hot water rinsed and then chromic acid rinsed.
- All metal parts are with matte black finish of at least 60 microns, for indoor use.
- Back and seat upholstery fabric with 3mm foam backing, finished with netting 15 g/m².
- Backrest and seat cover are equipped with zipper.

Fire Resistance

- Flammability compliance with California Bulletin 117 and international regulations in their last issue and particularly with safety regulations.
- Other regulations such as EN 1021, BS 7176, BS 5852 – upon request.

Warranty

- Refer to QGR Product Warranty.

Options

- Cupholder
- Seat numbering
- Row lettering
- Embroidery logo
- K-Roll castor system.
- Veneer varnishing wooden back outer